

July 28, 2003  
Case No. PHB 34,367 (7790/175)  
Serial No.: 09/616,635  
Filed: July 26, 2000  
Page 2

**CLAIM AMENDMENTS**

Claims 1-18 are currently pending in the application.

Please amend claim 1 as shown below.

The following listing of claims 1-18 will replace all prior versions, and listings, of claims in the application:

1. (Currently Amended) A body-worn personal communications apparatus, comprising:
- a physically-shortened electric antenna;
  - a transceiver connected to said physically-shortened electric antenna;
  - a microphone connected to said transceiver; and
  - a casing,
- wherein said transceiver is disposed within said casing, and
- wherein said physically-shortened electric antenna ~~and said microphone~~
- are is mounted on said casing, and
- wherein said microphone is mounted on said physically-shortened antenna.
2. (Previously Amended) The apparatus of claim 1, wherein said physically-shortened electric antenna is a helical antenna.
3. (Previously Amended) The apparatus of claim 1, wherein said physically-shortened electric antenna is a meander-line antenna.
4. (Previously Amended) The apparatus of claim 1, wherein said physically-shortened electric antenna is mounted transversely to a plane through said casing.

July 28, 2003  
Case No. PHB 34,367 (7790/175)  
Serial No.: 09/616,635  
Filed: July 26, 2000  
Page 3

5. (Previously Amended) The apparatus of claim 1, wherein said microphone is located at an end of said physically-shortened electric antenna furthest from said casing.
6. (Previously Amended) The apparatus of claim 5, wherein said physically-shortened electric antenna is formed from a coaxial cable that provides electrical connections between said microphone and said transceiver.
7. (Previously Amended) The apparatus of claim 5,  
wherein said physically-shortened electric antenna is formed from a hollow wire,  
wherein a first electrical connection between said microphone and said transceiver is provided by said hollow wire, and  
wherein a second electrical connection between said microphone and said transceiver is provided by a conductor enclosed by said hollow wire.
8. (Previously Amended) The apparatus of claim 6, wherein said microphone provides a low impedance at radio frequencies to thereby enable said coaxial cable forming said physically-shortened electric antenna to act as an inductive stub.
9. (Previously Amended) The apparatus of claim 5, wherein said microphone provides a top loading to said physically-shortened electric antenna.
10. (Previously Added) A body-worn personal communications apparatus, comprising:  
a casing;  
a physically-shortened electric antenna mounted on said casing; and  
a microphone mounted on said physically-shortened electric antenna.

July 28, 2003  
Case No. PHB 34,367 (7790/175)  
Serial No.: 09/616,635  
Filed: July 26, 2000  
Page 4

11. (Previously Added) The apparatus of claim 10, wherein said physically-shortened electric antenna is a helical antenna.

12. (Previously Added) The apparatus of claim 10, wherein said physically-shortened electric antenna is a meander-line antenna.

13. (Previously Added) The apparatus of claim 10, wherein said physically-shortened electric antenna is mounted transversely to a plane through said casing.

14. (Previously Added) The apparatus of claim 10, wherein said microphone is located at an end of said physically-shortened electric antenna furthest from said casing.

15. (Previously Added) The apparatus of claim 10, further comprising:  
a transceiver,

wherein said physically-shortened electric antenna is formed from a coaxial cable that provides electrical connections between said microphone and said transceiver.

16. (Previously Added) The apparatus of claim 15, wherein said microphone provides a low impedance at radio frequencies to thereby enable said coaxial cable forming said physically-shortened electric antenna to act as an inductive stub.

July 28, 2003  
Case No. PHB 34,367 (7790/175)  
Serial No.: 09/616,635  
Filed: July 26, 2000  
Page 5

17. (Previously Added) The apparatus of claim 10, further comprising:  
a transceiver,

wherein said physically-shortened electric antenna is formed from a  
hollow wire,

wherein a first electrical connection between said microphone and said  
transceiver is provided by said hollow wire, and

wherein a second electrical connection between said microphone and said  
transceiver is provided by a conductor enclosed by said hollow wire.

18 (Previously Added) The apparatus of claim 10, wherein said microphone  
provides a top loading to said physically-shortened electric antenna.